



### WEATHER-RITE™ CAR-SERIES Customized Air Handling Units

- 3,000 to 100,000 CFM.
- Custom-built to application requirements.
- Multiple filtration options including oil mist removal, charcoal, cartridge and bag filters.
- Direct-fired, indirect-fired, electric, hot water, or steam heat.
- Evaporative or mechanical cooling and dehumidification available.
- Fan options include forward or backward curved, airfoil or plenum.
- DDC/PLC controls available.



### WEATHER-RITE™ TT-SERIES Direct-Fired Air Handling Units

- 1,600 to 85,000 CFM.
- Rugged, all-welded construction.
- Variable volume discharge available.
- Upright or horizontal, indoor or outdoor configurations.
- Evaporative or mechanical cooling available.
- 100% outdoor air or variable return air/outdoor air arrangements.
- ETL certified in United States;  
100% outdoor air model only ETL certified in Canada.



### WEATHER-RITE™ XT-SERIES Direct-Fired Air Handling Units

- 1,000 to 60,000 CFM.
- Upright or horizontal, indoor or outdoor configurations.
- Choice of 100% make up air or outdoor air/return air arrangements.
- ETL certified in United States;  
100% outdoor air models only ETL certified in Canada.



### WEATHER-RITE™ STR-SERIES Indirect-Fired Air Turnover Units

- 4,500 to 100,000 CFM.
- Upright indoor configuration.
- System can achieve temperature differences as low as 3° F (-16° C) to 5° F (-15° C) throughout the space.
- Mechanical cooling available.
- ETL certified in United States and Canada.



### WEATHER-RITE™ IDF-SERIES Indirect-Fired Air Handling Units

- 3,500 to 57,000 CFM.
- Upright or horizontal, indoor or outdoor configurations.
- Choice of 100% make up air or outdoor air/return air arrangements.
- Evaporative or mechanical cooling available.
- ETL certified in United States and Canada.



### WEATHER-RITE™ NP-SERIES Negative Pressure, Low-Intensity Infrared Heaters

- Available in unitary heater inputs 40,000 - 200,000 Btu/h.
- Multiple heaters can be connected together to form a common vented multiburner system of up to 1.6 million Btu/h input.
- Vacuum design provides even heat distribution.
- CSA certified in United States and Canada.



### WEATHER-RITE™ BH-SERIES Economical Positive Pressure Low-Intensity, Unitary Infrared Heaters

- 40,000 to 200,000 Btu/h inputs.
- Design flexibility with L- and U-tube options and broad range of burner sizes and tube lengths.
- Continuous aluminum reflector (without gaps) and end caps are standard.
- Hot rolled or aluminized steel tubing.
- CSA certified in United States and Canada.

### WEATHER-RITE™ GH-SERIES Factory-Assembled, Low-Intensity Infrared Heaters

- 30,000, 40,000 and 50,000 Btu/h inputs.
- Compact u-tube design provides maximum inputs and minimum lengths.
- Factory assembled for easy installation.
- One building penetration – balanced flue for both exhaust and combustion air.
- Horizontal concentric venting and thermostat provided with unit.
- CSA certified in United States and Canada.

### WEATHER-RITE™ UHA-SERIES Axial Fan Unit Heaters

- 30,000 to 385,000 Btu/h inputs.
- 82% efficiency with tubular heat exchangers and power vent.
- Non-separated or separated combustion units.
- Stainless steel heat exchanger option.
- Remote fan operation for summer air circulation.
- CSA certified in United States and Canada.



### WEATHER-RITE™ UHD-SERIES Duct Furnaces

- 75,000 to 385,000 Btu/h inputs.
- 82% efficiency with tubular heat exchangers and power vent.
- Non-separated or separated combustion units.
- Approved for installation down stream of refrigeration system with optional stainless steel heat exchangers and drain pan (Models UHDX[S]R 150-400 only).
- CSA certified in United States and Canada.



#### Installation Code and Annual Inspections:

All installation and service of WEATHER-RITE™ equipment must be performed by a contractor qualified in the installation and service of equipment sold and supplied by Weather-Rite LLC and conform to all requirements set forth in the WEATHER-RITE™ manuals and all applicable governmental authorities pertaining to the installation, service and operation of the equipment. To help facilitate optimum performance and safety, Weather-Rite LLC recommends that a qualified contractor conduct, at a minimum, annual inspections of your WEATHER-RITE™ equipment and perform service where necessary, using only replacement parts sold and supplied by Weather-Rite LLC.

**Further Information:** Applications, engineering and detailed guidance on systems design, installation and equipment performance is available through WEATHER-RITE™ representatives. Please contact us for any further information you may require, including the Installation, Operation and Service Manual.

#### Weather-Rite LLC

616 North 5th Street  
Minneapolis, MN 55401  
Telephone: +1.612.338.1401  
Fax: +1.612.338.6783  
Toll Free: 1.800.589.3691  
[www.weather-rite.com](http://www.weather-rite.com)

**These products (with the exception of the CGTH and UHA[X][S]30-75) are not for residential use.  
This document is intended to assist licensed professionals in the exercise of their professional judgment.**

© 2010 Weather-Rite LLC All rights reserved. No part of this work covered by the copyrights herein may be reproduced or copied in any form or by any means – graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems without written permission of Weather-Rite LLC.